



FABRIC BOND 930

DESCRIPTION:

Fabric Bond 930 is designed to be a bonding agent to secure polyester fabric to roof surfaces.

ADVANTAGES:

- Seals asphaltic surfaces with little or no bleed through
- Excellent adhesion to various surfaces
- Easy to use, easy clean up, non-toxic, and VOC compliant water based coating
- Must be top coated with an American WeatherStar top coat

BASIC USES:

Great as a primer over asphalt, concrete, wood, tile, metal, and virtually any clean, dry, non-silicone surface. Also used for installing fabric to any roof surface before applying top coat.

INSTALLATION:

- **Surface Prep:** All surfaces to be coated must be clean, dry and free of any oil, grease or dirt. Pressure washing is recommended for older coatings. Do not apply within two hours of sunset, rain, fog, or freezing temperatures.
- **Mixing:** Fabric Bond 930 is ready to use. Thinning is not required nor recommended.
- **Spray:** Airless sprayer, 2000 psi, 2 gpm capacity with a #027-#031 tip
- **Brush:** High-quality synthetic bristle brush
- **Roller:** Size depends on surface condition—short nap for smooth surfaces, medium nap for more porous surfaces

WARRANTY:

American WeatherStar warrants that the material supplied will meet or exceed physical properties as published. The contractor guarantees that workmanship will be free of defects in coating application. Since performance of previously installed substrate is beyond the control of American WeatherStar or the contractor, requests for additional warranty coverage shall be subject to prior approval by American WeatherStar.

TECHNICAL DATA:

COLOR:	Blue
VISCOSITY:	600-800 CPS
WEIGHT:	8.38 lbs. per gallon
PERCENT SOLIDS BY WEIGHT:	48% ± 2%
FLASH POINT:	N/A
DRY TIME:	12-24 hours
PACKAGING:	5 gallon

MAINTENANCE:

Periodic maintenance of all American WeatherStar systems and products, including cleaning, is recommended to ensure extended service life and help to improve product performance.

SAFETY INFORMATION:

Read the Safety Data Sheet (SDS) and container labels for detailed health and safety information. This product is intended for industrial use by properly trained professional applicators only.

AMERICAN WEATHERSTAR LLC

8095 Padgett Switch Rd. | Irvington, AL 36544 | USA
www.americanweatherstar.com | info@americanweatherstar.com
 Toll Free: 800-771-6643 | Fax: 251-479-3602