



ECOCLEANER 925

DESCRIPTION

EcoCleaner 925 is a unique, high-performance, and environmentally friendly cleaner. Its biodegradable formulation meets all US VOC regulations, including the most stringent Southern California regulations. EcoCleaner 925 is a low-foaming formulation that features significant renewable content. With its exceptional cleaning ability, EcoCleaner 925 will even remove paints and adhesives when used at full strength.

BASIC USES

Diluted 5:1 for effective cleaning of most surfaces including roofs decks, concrete, and steel. EcoCleaner 925 may be used at lower dilutions for tougher stains and soiling. Old paints and adhesives may be removed with minimal or no dilutions.

INSTALLATION

Apply diluted EcoCleaner 925 with a low-pressure sprayer—such as a garden sprayer—at a rate of 1 gal per 150 sq. ft. Power wash all surfaces with a minimum of 3,000 psi using a wide fax tip. Failure to use a power washer will result in poor coating adhesion. Rinse completely. Water should be clear with no soap bubbles.

STORAGE AND SHELF LIFE

EcoCleaner 925 has a recommended shelf life of 12 months from date of manufacture when stored in unopened containers and between 40° F and 80° F.

WARRANTY

American WeatherStar warrants that the material supplied will meet or exceed physical properties as published. The contractor guarantees that workmanship will be free of defects in coating application. Since performance of previously installed substrate is beyond the control of American WeatherStar or the contractor, requests for additional warranty coverage shall be subject to prior approval by American WeatherStar.

TECHNICAL DATA

WEIGHT:	8.3 lbs./gal, ASTM 1475
FLASH POINT:	> 212°F, ASTM D 1310
VOC:	0 grams/liter, ASTM D Method 24
MINIMUM APPLICATION TEMP.:	40°F
SHELF LIFE:	12 months unopened container
PACKAGING:	5 gallon

SAFETY INFORMATION

Read the Safety Data Sheet (SDS) and container labels for detailed health and safety information. This product is intended for industrial use by properly trained professional applicators only.

AMERICAN WEATHERSTAR LLC

8095 Padgett Switch Rd. | Irvington, AL 36544 | USA
www.americanweatherstar.com | info@americanweatherstar.com
Toll Free: 800-771-6643 | Fax: 251-479-3602